



Art. Nr. 00112293

LED-Klemmleuchte "SL49", Tageslicht/Dimmer

Anlaufzeit bis zur Erreichung von 60% des vollen Lichtstroms (max.)	1 s
Verwendung	Innenräume
Zündzeit (max.)	0,3 s
Zahl der Schaltzyklen bis zum vorzeitigen Ausfall (min.)	10000
Max. Höhe	69 cm
Lichtfarbe	Tageslicht
Leistungsaufnahme	7,8 VA
Farbwiedergabeindex RA (min.)	80
Min. Höhe	48,5 cm
Frequenz	60 Hz, 50 Hz
EAR Reg.Nr.	DE 38720470
Lampenlebensdauerfaktor bei 6000h (min.)	0,9
Gewicht	540 gr
Farbtemperatur	6500 K
Stromanschluss-Steckertyp	Eurostecker, Typ C (CEE 7/16)
Max. Primärstrom Vorschaltgerät	0,2 A
Lichtstromerhalt bei 6000h	0,8
Ausführung Vorschaltgerät	Konstantstrom
Nom. Ausgangsspannung Vorschaltgerät	24 V
Abstrahlwinkel	100 °
Dimmbarfunktion	3 stufig
Lebensdauer	20000 h
Lichtstrom	480 lm
Spitzenlichtstärke	180 cd
Umgebungstemperaturbereich	25 °C
Anzahl Gelenke	3
Ausleger min.	30 cm
Ausleger max.	67 cm
Elektrischer Leistungsfaktor der Lampe (min.)	0,767
Max. Ausgangsstrom Vorschaltgerät	0,28 A
Betriebsspannung Vorschaltgerät	100-240 V
Ausführung	Schreibtischleuchte
Betriebsspannung (DC)	24 V



Item no. 00112293

LED Clamp Lamp "SL49", daylight/dimmer

Start-Up Time Until 60% of Full Light Output Has Been Reached (max.)	1 s
Usage	Interior Rooms
Starting Time (max.)	0.3 s
Number of Switching Cycles until Premature Failure (min.)	10000
Maximum Height	69 cm
Light Colour	Daylight
Power Consumption	7.8 VA
Colour Reproduction Index RA (min.)	80
Minimum Height	48,5 cm
Frequency	60 Hz, 50 Hz
EAR Reg.No.	DE 38720470
Lamp Survival Factor at 6000h (min.)	0,9
Weight	540 gr
Colour Temperature	6500 K
Power connector plug type	Euro Plug, Type C (CEE 7/16)
Max. Primary current AC-Adapter	0.2 A
Lamp Lumen Maintenance Factor at 6000h	0.8
Excution AC Adapter	Constant Current
Nom. Output voltage AC-Adapter	24 V
Beam angle	100 °
Dimm function	3 Levels
Life	20000 h
Luminous flux	480 lm
Peak intensity	180 cd
Ambient temperature range	25 °C
Number of Joints	3
Boom min.	30 cm
Boom max.	67 cm
Electrical Efficiency Factor of the Bulb (min.)	0,767
Max. Output current AC-Adapter	0,28 A
Voltage AC-Adapter	100-240 V
Model	Desk Lamp
Operating Voltage (DC)	24 V